



Applications

PROCESS WEIGHING

- Batching/Blending
- Filling/Dispensing
- Bulk Bag

Features

WAVERSAVER®

- Ignores vibration on and around scales

C2® Electronic Calibration

- Electronic calibration without test weights



INTEGRATED TECHNICIAN®

- Weighing system monitoring and troubleshooting

SMM-SD (Secure Memory Module with SD RAM)

- Expandable automatic backup of configuration data for easy transfer to other instruments or your PC

Network Flexibility

- Connect via common plant networks
- Use it as a DeviceNet Master
- Use it as a gateway between networks

The Hardy HI 3010 can act as standalone controller, or as a sub-routine in your PLC, PC or DCS Ladder Logic system for a variety of applications such as filling, dispensing, or intermediate bulk container (IBC). It powers the scale, controls the speed, evaluates the weight, automatically refills and discharges the desired amount of product and notifies you of errors through its extensive networking capabilities.

FLEXIBLE DESIGN

- Designed to fit nearly any filling, dispensing, or Intermediate Bulk Container Application
- Handles all materials from all types of feeding mechanisms (gates, feeders, or valves) to all types of destination (packages, containers, vessels, or trucks)

CONFIGURABLE CONTROL

- **No programming required:** This Filler/Dispenser provides one-stop application control with less operator intervention and fewer additional hardware requirements. Need a function? Just turn it on, whether it is multi-speed, auto-refill or discharge, auto in-flight comp, material jog, feed timer limits, vibrators... Well, you get the picture.
- **Blind Remote:** No need for a front console and display for hard-to-access installations. Just use the HI 3010R Blind Remote with an optional built-in junction box. Configure or monitor it from the office or the plant floor, using a web browser on a PC.

- **Ease of Networking:** Need to communicate to your PLC using a standard control network? The HI 3010 can use all standard protocols. Let the HI 3010 be the subroutine in your PLC Ladder Logic Control. No Network? No Problem! The Filler/Dispenser can operate stand-alone or in conjunction with other 3000 Series controllers in a Hardy Control-Link Network with "Plug and Play" implementation.

SMART CONTROL

- **Efficient and accurate filling control:** Built-in features such as multiple speeds, Auto Fast Feed Adjust, self-adjusting preacts, and auto jog functions to auto-tune your process. These features continuously improve product throughput and let you focus on the bigger picture.
- **On-board storage and totalizers:** Store different setups with total weights and number of fills or discharges. Access this data from the front panel or a web browser to ensure consistency and eliminate operator error.
- **Complete Flexibility:** With its flexible I/O mapping, you can direct any parameter to a local output or to any point on the plant network. You can even have an event emailed directly to you.

COMPONENTS TO COMPLETE YOUR HARDY SYSTEM

Hardy Bench Scales, Floor Scales and Load Points

Hardy carries a wide variety of strain gauge load points and scale bases to accommodate your application requirements.

OneMount™ Load Point with C2 Calibration



Hardy Bench Scales




Allen-Bradley® Compatible Plug-in Weigh Scale Modules



HI 3000 Series
HI 4050 Controllers and
HI 6000 Series



NETWORK CONFIGURATIONS



SPECIFICATIONS

Display

- 4 line x 20 character backlit LCD
- 5 x 7 dot matrix

Update Rate

- 55 times per second

Averaging

- Sliding up to 250 readings in single unit increments

Resolution

- Display: 1:985,000 (3mV/V load cells)
- Internal: 1:1,048,000

Standard Interfaces

- Ethernet: 1 CP/IP; embedded web server
- Serial RS-232: simplex to printer

Stable Weight Reading

- WAVESSAVER® 0.25Hz minimum

Calibration Techniques

- C2® electronic calibration
- Traditional calibration with test weights

Instrument Local I/O

- Five mappable inputs optically isolated
- Four or seven mappable outputs 48-240VAC Form A
- Third party mappable over DeviceNet

Load Point Excitation

- 5VDC power drives up to 16 350-ohm load cells

Power Requirement

- 108-264VAC, 47-63Hz or 12-24 VDC
- 25 watts max

Operating Temperature

- -10° to +50°C (14° to 122°F)

Storage Temperature

- -20° to +70°C (-4° to 158°F)

Enclosure

- Panel mount
- Swivel mount

Dimensions

- Panel mount: 6.03" (153mm) with rear cap
- Panel cutout: 8.94" W x 6.63" H (227mm W x 169mm H)

Approvals

- CE, UL/CUL

Warranty


- Two-year warranty against defects in workmanship

All specifications subject to change without notice. Please contact the Hardy factory or visit our website for the latest specifications.

All information within is subject to change without notice. Visit our website for latest specifications. WAVESSAVER, C2, IT, ADVANTAGE and ANY-WEIGH are registered trademarks of Hardy Process Solutions, Inc.. Allen-Bradley, CompactLogix, MicroLogix and Encompass are trademarks of Rockwell Automation, Inc. All other trademarks or registered trademarks are the property of their respective owners.

www.hardysolutions.com • 800.821.5831

HARDY CONTROL-LINK NETWORK



MODELS

HI 3010: Includes keyboard & LCD display

HI 3010R: Blind remote; no keyboard or display

OPTIONS

- Built-in junction box
- Environmental rear cap
- Swivel mount bracket
- Smart Diagnostics
- Dual Channel Analog Out
- ControlNet
- DeviceNet
- Modbus TCP
- Profibus
- OPC
- EtherNet /IP
- DC or AC power
- DC or AC relay outputs

Hardy Process Solutions

10075 Mesa Rim Rd.
San Diego, CA 92121
tel. +1-858-278-2900
tel. 800-821-5831
fax +1-858-278-6700
www.hardysolutions.com
hardyinfo@hardysolutions.com



HI 3010 0222
0400-0015-01C